

Features



- Available In Short (S = 25 mm), Medium (M = 40 mm) and Long (L = 48 mm) Nose Working Length for Dierent Applications
- Comfortable Ergonomic Rubber Handle
- Light Weight and Well Balanced
- Adjustable Exhaust Deflector
- Steel Casted Trigger for Enhanced Durability
- Low Noise

Applications

- Bag Closure
- Cage Grid Secure
- Auto Seat
- Wire Mesh Closure
- Label Attachment
- Spring Bed / Mattress

Tool Specifications



| Model | W L | C-Ring Type |  |  | Tool Weight | Magazine Capacity | Similar to Meihotech | Similar to Stanley |
|-------------|----------------|------------------------------------|---|---|--------------------------------|-------------------|----------------------|---------------------|
| LPHC-A815-S | 25 mm 1" | Ø 1.8 mm .070" 15 Gauge 15G100 | 19 mm 3/4" | 7.9 - 10.7 mm 5/16 - 13/32" | 1.40 kgs 0.64 lbs | 100 pcs | MC-6, MC-6W | SC7 |
| LPHC-A815-M | 40 mm 9/16" | | | | 1.45 kgs 0.66 lbs | | | |
| LPHC-A815-L | 48 mm 2" | | | | 1.50 kgs 0.68 lbs | | SC77XE | |
| LPHC-A515-S | 25 mm 1" | | | | 4.8 - 8.7 mm 3/16" - 11/32" | | 1.40 kgs 0.64 lbs | MC-6CA, MC-6CALW |
| LPHC-A816-S | 25 mm 1" | Ø 1.6 mm .063" 16 Gauge 16G110 | 12.5 mm 1/2" | 7.9 - 10.7 mm 5/16 - 13/32" | 1.40 kgs 0.64 lbs | 110 pcs | | |
| LPHC-A816-M | 40 mm 9/16" | | | | 1.45 kgs 0.66 lbs | | | |
| LPHC-A816-L | 48 mm 2" | | | | 1.50 kgs 0.68 lbs | | | |
| LPHC-A516-S | 25 mm 1" | | | | 4.8 - 8.7 mm 3/16" - 11/32" | | | |
| LPHC-C316-S | 25 mm 1" | Ø 1.6 mm .063" 16 Gauge 516G100 | 12.5 mm 1/2" | 3.2 - 5.6 mm 1/8 - 7/32" | 1.40 kgs 0.64 lbs | 100 pcs | MC-660 | SC760 |

U TECH FASTEN PVT. LTD.

Plot No. 179, GIDC Estate, Waghodia, Vadodara, Gujarat - 391760 (India)

ph.: +91 2668 263636, 9372747114

fax: +91 2668 263635

e-mail: yogeshn.utech@gmail.com

website: www.utechfasten.in