

# SP50 Series

## Specialty Tools

Pneumatic Stapling Pliers




U TECH FASTEN PVT. LTD.




CL Anvil


### SP103020




### SB5019



### 777



### 779



### Features

- Powerful Shuttle Blade Provides Pre-Compression Prior to and During The Stapling Operating - Giving A Strong, Tight Closure Without Breaking The Corrugated Surface
- 6" x 1" High Throat Allows Flexibility of Staple Placement and Limits Interference from Obstacles Such As Box Flanges
- C Anvils (CL or CR Available for Sealing Partial Overlap Cartons Penetrates and Securely Fastens up to 2 Thicknesses of Double - Wall: 2x AB Flute or 4x C Flute Boards (A Flute = 3/16" or 4.8 mm Thick) (B Flute = 1/8" or 3.2 mm Thick) (C Flute = 5/32" or 4.0 mm Thick)

### Fasteners

Tools	Staple Type	Similar to	Crown Size	Shank Diameter	Leg Length	Load Capacity
SP50-10B-A	SB 103020	Bostitch SB 103020	12.95 mm 1/2"	0.50 x 2.60 mm .020 x .103"	10, 12, 15 mm 3/8, 1/2, 5/8"	102
SP50-5B-A	SB 5019	Bostitch SB 5019	12.85 mm 1/2"	0.48 x 1.25 mm .019 x .050"	6, 10, 12, 15 mm 1/4, 3/8, 1/2, 5/8"	108
SP50-777-A	777	JK 777	12.3 mm 1/2"	0.65 x 2.25 mm .026 x .090"	10, 12, 15 mm 3/8, 1/2, 5/8"	140
SP50-779-A	779	JK 779	12.3 mm 1/2"	0.63 x 1.3 mm .025 x .050"	8, 10, 12, 14, 16 mm 5/16, 3/8, 1/2, 9/16, 5/8"	125

### Applications

- Corrugated Containers
- Trays & Lids
- End Caps
- Headers & Bags
- Container Inserts
- Bedding

### Tool Specifications

Weight	Dimensions (L x W x H)	Operating Pressure
2.2 kg	370 x 55 x 240 mm	2.5 - 3.9 kg / cm <sup>2</sup>
4.8 lbs	14 1/2 x 2 1/8 x 9 1/2"	36 - 55 psi

### U TECH FASTEN PVT. LTD.

Plot No. 179, GIDC Estate, Waghodia, Vadodara, Gujarat - 391760 (India)

ph.: +91 2668 263636, 9372747114

fax: +91 2668 263635

e-mail: yogeshn.utech@gmail.com

website: www.utechfasten.in